



Automotive Wheel/Tire Cleaner

WT %

- 68.0 Water
- 10.0 SoyGold 2000
- 6.0 Witconate 1240 (Witco)
- 5.0 Glycol Ether EB
- 5.0 Sodium Xylene Sulfonate (SXS)
- 3.0 Igepal CO-630 (Rhodia)
- 2.0 Sodium Metasilicate Pentahydrate
- 1.0 Sodium Tripolyphosphate (STPP)

Blending Procedure:

1. Combine Water, Sodium Metasilicate and mix until completely dissolved.
2. Add STPP and mix until completely dissolved.
3. Add EB, Witconate 1240, Igepal CO-630, and mix until homogeneous.
4. Slowly begin to add SoyGold 2000. Once all SoyGold has been dispersed, begin to titrate in the SXS until clear.

The information given in this formulary is to the best of our knowledge accurate. The formulations are intended to be helpful, but no warranty is expressed or implied regarding the accuracy of the data. It is the users responsibility to determine the suitability of his use of the products described herein, and since the conditions of use are out of our control, we disclaim all liability with respect to the use of any materials supplied by AEP. Nothing contained herein shall be construed as permission or as a recommendation to practice any patented invention without a license from the patent owner nor as a recommendation to use any product or to practice any process in violation of any law or any government regulations.